

GKB Diplomat™ D3622 IP Camera

Self-Networking Megapixel IP Vandal-proof Dome Camera with PoE

GKB Diplomat™ D3622 is a professional 1.3 Megapixel IP vandal-proof dome camera and targeting large or tender-based installation projects requiring advanced network technologies. It is also the world's first professional network camera to feature automated self-networking for fast network set-up and installation.

Features:

- **1.3 Megapixel CMOS Sensor**

GKB Diplomat™ D3622 is a professional 1.3 Megapixel IP Camera and provides SXGA resolution. One GKB Diplomat™ D02 covers the resolution over 4 times of D1 resolution analog cameras.

- **H.264 Video Compression**

GKB Diplomat™ D3622 features H.264 video compression for superior video resolution. The low bit-rate of H.264 codec makes for smoother video streaming, even under the most unfavorable of network environments.

- **Digital Zoom Function**

GKB Diplomat™ D3622 features 1.3 Megapixel high resolution. Bundled GKB Envoy™ software which provides Digital Zoom Function, users are able to see clear live view image in all surveillance area by using few cameras.

- **Automated Self-Networking**

GKB Diplomat™ D3622 is a self-networking IP camera that eliminates the need for complicated and time-consuming router configuration. Bundled GKB Envoy™ software reduces network set-up to less than 30 seconds.

- **Cloud Platform**

Cloud platform framework brings IP solution to a new level. The IP cameras are managed by account and password. The live image and playback can display anytime anywhere via the IE browser, without any extra software installed.

- **Micro-SD Card Storage**

GKB Diplomat™ D3622 is equipped with a Micro-SD card slot. The video is recorded locally in the Micro-SD card, and can be retrieved easily remotely by IE browser without taking out the Micro-SD card.



GKB Diplomat™ D3622 IP Camera

Video	Image Sensor	1/3" Megapixel CMOS Sensor	
	Video Compression	H.264	
	Video Streams	8	
	Resolution	SXGA(1280*1024),VGA,QVGA	
	Frame Rate	Up to SXGA, 15 fps or VGA, 30 fps	
	Min. Illumination	0.5 Lux at F1.0 (2400 °K, 30 IRE)	
	Gamma	0.45	
	S/N Ratio	>44 dB	
	Scanning System	Progressive	
	Shutter Control	1/5~1/15,000 sec Electronic rolling shutter(ERS)	
	Night Mode	C/B mode auto switched with ICR (Under 5-7 Lux)	
	Auto Gain Control	Auto	
	Back Light Control	Auto	
	White Balance	Auto / Manual(by remote software)	
Audio	Audio Streaming	2 way, GSM Encoder 13 kbits/s	
	Audio Input / Output	Audio in: Line Level Input DC 3V, 20Hz-4KHZ, 1 Vrms / Audio out: Line Level Output, Speaker 8 ohm 330mW	
Power	Power Supply	DC-12V OR Power over Ethernet (IEEE 802.3af) Max=5W (Auto Switch between DC 12V & PoE)	
	Power Consumption		
Lens	4.3mm; 6mm Board Mega Pixel Lens		
IR-Cut Filter	Built-in ICR		
Storage	Micro SD Card up to 32GB (Enable Remote Site Playback)		
Dimension	110 (H) x 140 (ø) mm		
Weight	1100g		
Operating Temperature	-20°C ~ 60°C		
Impact Protection	Yes		

Networking	Protocol	HTTP,TCP,UDP,DNS,DHCP,PPPoE, Samba,RTP,RTCP,RTSP	
	Ethernet	10/100Mbps Fast Ethernet RJ-45 port	
Software	Operating System	Windows XP and above	
	Software Package	NVR-10: 64 Channel NVR	Viewer-10
		NAS & SD Card Remote Playback Supported	Setup Software Utility

Dimension (mm)

